



# COMPACTION ROLLERS

1450

3000

4000



- Easy to Operate, Easy to Maintain
- Perfect Blend of Weight, Wheel Base, and Drum Diameter
- Operate in Static or Vibratory Mode (Including 1-1/4-Ton 1450 Model)
- Feature:
  - Hydrostatic Drive
  - Split Front Drums
  - Automotive Steering Linkage
  - Non-Corrosive Polyethylene Tank
  - Optional Towing Wheels

[www.4aMauldin.com](http://www.4aMauldin.com)

MAULDIN®

Specifications	1450-S	1450	3000	4000		1450-S	1450	3000	4000
<b>Operation</b>					<b>Drums</b>				
Engine	18 HP Kohler	18 HP Kohler	18 HP Kohler	18 HP Kohler	Front: Type	Split	Split	Split	Split
Brakes—Service —Parking	Dynamic Caliper Disc	Dynamic Caliper Disc	Dynamic Caliper Disc	Dynamic Caliper Disc	Thickness	3/8"	3/8"	1/2"	3/4"
Drive System	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Width	28"	28"	28"	28"
Travel Speed	0–6 MHP	0–6 MHP	0–6 MHP	0–6 MHP	Diameter	20"	20"	20"	20"
Fuel Capacity	5 Gal.	5 Gal.	5 Gal.	5 Gal.	Oscillation	22°	22°	22°	22°
Hyd. Oil Capacity	8 Gal.	8 Gal.	8 Gal.	8 Gal.	Rear: Thickness	3/8"	3/8"	1/2"	3/4"
Water Capacity	42 Gal.	42 Gal.	42 Gal.	42 Gal.	Width, Chain Drive	34.5"	34.5"	34.5"	34.5"
Steering	Auto. Type	Auto. Type	Auto. Type	Auto. Type	Width, Planetary Drive	36"	36"	36"	36"
					Diameter	24"	24"	24"	24"
<b>Dimensions</b>					<b>Water System</b>				
Length	83"	83"	83"	83"	Tank Type	Polyethylene Gravity	Polyethylene Gravity	Polyethylene Gravity	Polyethylene Gravity
Width	38"	38"	38.5"	39"	Cocoa Mats	Yes	Yes	Yes	Yes
Height	59"	59"	59.5"	60"	Scrapers	Yes	Yes	Yes	Yes
Wheelbase	56.5"	56.5"	56.5"	56.5"	<b>Compactive Effect</b>				
Curb Clearance	8.5"	8.5"	8.5"	8.5"	Amplitude	<i>(Static Operation Only)</i>	.022	.022	.022
Wall Clearance	1.25"	1.25"	1.25"	1.25"	Vibration (VPM) Centrifugal Force		0–3,600 2,665 lbs.	0–3,600 2,665 lbs.	0–3,600 2,665 lbs.
Turning Radius Inside	10'9"	10'9"	10'9"	10'9"	<b>Options</b>				
<b>Weight</b>					• Diesel Engine	• Electronic Instrumentation	• Hydraulic Towing Package		
Empty Weight	1,875 lbs.	1,875 lbs.	2,170 lbs.	3,170 lbs.	• Special Paint	• Pressurized Water			
Loaded Weight	2,475 lbs.	2,475 lbs.	3,000 lbs.	4,000 lbs.					

Specifications subject to change without notice.



## Mauldin Brothers Equipment, Inc.

2499 Rutherford Road ■ Greenville SC 29609

864.244.4800 ■ Fax 864.244.5007 ■ E-mail SalesInfo@4aMauldin.com