



WORLD CLASS CONSTRUCTION EQUIPMENT

®

MAULDIN
PAVING PRODUCTS

250 & 500 GALLON TRAILER MOUNT HOT TACK SPRAYERS



CALDER BROTHERS CORPORATION
48 Donkle Road
Greenville, SC 29609
Tel: (864) 244-4800
Fax: (864) 244-5007

www.4aMauldin.com



®

MAULDIN

PAVING PRODUCTS

WORLD CLASS CONSTRUCTION EQUIPMENT

FEATURES & BENEFITS

- 5.5hp Honda engine.
- 1-1/2" draincock conveniently located at rear of machine.
- Material temperature thermometer, 50°F to 550°F (10°C to 287°C) with protective guard and located at the front of the unit for easy view by the operator.
- Frame is constructed of heavy duty channel iron.
- Wide track industrial axle with leaf spring suspension for ease of towing, low profile, low centre of gravity and lower unloading height.
- 10" diameter top filling manhole assembly.
- Asphalt gear pump with a capacity of 10 gallons per minute.
- Heavy duty adjustable external relief valve to obtain desired spraying pressure and volume.
- Direct drive system complete with coupler guard.
- Flushing tank for easy and convenient cleanout.
- 5ft hand held spray wand with quarter turn control valve, spray nozzle and 40 feet of hi-pressure hose mounted on a Hose reel.
- Two 50,000btu propane burners.
- Electric brakes.
- Adjustable hitch comes with 2-3/4" pintle.
- 3/8" x 4' trailer safety chains.
- Adjustable swivel jack leg.
- Exhaust stacks equipped with rain covers.

Options

- MT-250: 6ft spray bar comes with 9hp Honda engine and 18gpm pumping system.
- MT-500: 8ft spray bar comes with 11hp Honda engine and 25gpm pumping system.

Specifications	MT-250	MT-500
Shipping Weight	1075lbs (795 kg)	2000lbs (907 kg)
Dimensions		
Overall Length:	115" (2921 mm)	154" (3911 mm)
Overall Width:	72" (1829 mm)	67" (1701 mm)
Loading Height:	46" (1168 mm)	53" (1346 mm)
Capacity	250 gal (945 L)	500 gal (1893 L)
Engine	5.5hp Honda	5.5hp Honda
Pump	10gpm	10gpm
Burners Vapor propane	Two 50,000Btu	Two 50,000Btu
Suspension		
Axle	Single	Tandem
Capacity	3500lb (1590 kg)	3500lb (1590 kg)
Tires	(2) 225/75R15	(2) 225/75R15

